

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Hot 4-in-1 Heating Oil Treatment**

Product Code(s) : US Product Codes: 00161, 90161, 00164, 90164, 00163
Canada Product Codes: 00221, 90221

Recommended use of the chemical and restrictions on use

: Fuel oil treatment. No restrictions on use known.

Chemical family : Mixture.

Name, address, and telephone number of the manufacturer:

FPPF Chemical Company, Inc.

117 West Tupper Street
Buffalo, NY, USA
14201

Manufacturer's Telephone # : 1-800-735-3773

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.).

Name, address, and telephone number of the supplier:

Refer to manufacturer

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Amber liquid. Odour: Mineral oil

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification

Flammable Liquid - Category 4
Acute Toxicity, oral - Category 4
Acute Toxicity, dermal - Category 3
Acute Toxicity, inhalation - Category 3 (vapor)
Skin Irritation - Category 2
Eye Damage/Irritation - Category 2A
Aspiration Toxicity - Category 1
Reproductive Toxicity - Category 2 Developmental
Carcinogenicity- Category 2
Specific Target Organ Toxicity, Single Exposure - Category 3 (cns)
Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory)

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

Hazard statement(s)

SAFETY DATA SHEET

Combustible liquid and vapor.
 Harmful if swallowed.
 Toxic in contact with skin.
 Toxic if inhaled.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause respiratory irritation.
 May cause drowsiness and dizziness.
 May be fatal if swallowed and enters airways.
 Suspected of causing cancer.
 Suspected of damaging the unborn child.

Precautionary statement(s)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from flames and hot surfaces. Avoid breathing vapors or mists. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Wash hands and face thoroughly after handling.

In case of fire, use water fog, dry chemical, CO₂ or 'alcohol' foam.

IF EXPOSED OR CONCERNED: Get medical attention/advice.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Take off contaminated clothing and wash before re-use.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Rinse mouth.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification: May be sensitive to static discharge. Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| <u>Chemical name</u> | <u>Common name and synonyms</u> | <u>CAS #</u> | <u>Concentration</u> |
|--------------------------------|---|--------------|----------------------|
| Light aromatic solvent naphtha | Aromatic Naphtha Solvent naphtha (petroleum) light aromatic | 64742-95-6 | 25.0 - 40.0 |
| 2-Butoxy ethanol | Ethylene Glycol Monobutyl Ether EB | 111-76-2 | 45.0 - 55.0 |
| 1,2,4-Trimethylbenzene | Pseudocumene | 95-63-6 | 4.0 - 6.5 |
| 1,3,5-Trimethyl benzene | Trimethylbenzol Mesitylene | 108-67-8 | 2.0 - 4.0 |
| Xylene (mixed isomers) | Dimethylbenzene Methyltoluene Xylol | 1330-20-7 | 1.0 - 2.0 |
| Cumeme | Isopropyl benzene Cumol, 2-phenyl propane | 98-82-8 | 0.1 - 0.9 |
| oleic acid | Oleic acid; 9-Octadecenoic acid; Elaic acid | 112-80-1 | 0.1 - 0.9 |
| Heavy aromatic solvent naphtha | Aromatic Naphtha Solvent naphtha (petroleum) heavy aromatic | 64742-94-5 | 0.1 - 0.9 |

SAFETY DATA SHEET

| | | | |
|--------------------------|---|------------|------------------|
| Trimethylbenzenes | Methylxylenes (non-specific name); Trimethylbenzenes (non-specific name) | 25551-13-7 | 1.0 - 2.0 |
| Ethylbenzene | Ethylbenzene Phenylethane EB | 100-41-4 | 0.1 - 0.5 |

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Rinse mouth. Aspiration hazard Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only.
- Skin contact* : IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Most important symptoms and effects, both acute and delayed

- : IF exposed or concerned: Get medical attention/advice.
Harmful if swallowed. Symptoms may include severe abdominal pain, nausea and vomiting. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Toxic in contact with skin. May be absorbed through the skin, producing symptoms similar to ingestion or inhalation.
Toxic if inhaled. Symptoms may include coughing, choking and wheezing. May cause respiratory impairment and lung damage.
May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties.
May cause drowsiness or dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.
Causes skin irritation. Symptoms may include redness, itching and swelling.
Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.
May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing.
Symptoms include coughing, shortness of breath and wheezing.
Suspected of causing cancer. Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing.
Suspected of damaging the unborn child. Symptoms in offspring may include reduced fetal weight, behavioral effects, delayed skeletal formation and hearing loss.
- Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights. Chronic overexposure to 2-butoxyethanol may cause liver, kidney and blood damage, based on animal data. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Provide general supportive measures and treat symptomatically. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Dry chemical, foam, carbon dioxide and water fog.

SAFETY DATA SHEET

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Combustible liquid and vapour. Keep away from flames and hot surfaces. - No smoking. Use only outdoors or in a well-ventilated area. May be sensitive to static discharge. After prolonged storage, may release explosive peroxides in the presence of air. Rate of peroxide formation is not known. Vapors may travel considerable distance to a source of ignition and flash back. Vapours may be heavier than air and may collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquid - Category 4

Hazardous combustion products

- : Carbon oxides. Nitrogen oxides. Reactive hydrocarbons. Aldehydes. Other irritating fumes and smoke.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

- : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Pick up and transfer to properly labelled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

Special spill response procedures

- : In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ):
Xylene (100 lbs / 45.4 kg);
Cumene (5000 lbs / 2270 kg);
Ethylbenzene (1000 lbs / 454 kg)

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

SAFETY DATA SHEET

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from flames and hot surfaces. - No smoking. Wear protective gloves/clothing and eye/face protection. Wash hands thoroughly after handling. Avoid breathing mist or vapours. Do not eat, drink or smoke when using this product. Do not ingest. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.
- Conditions for safe storage** : Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up. Take measures to prevent the build up of electrostatic charge. Store away from incompatibles and out of direct sunlight. After prolonged storage, may release explosive peroxides in the presence of air. Direct sunlight or heat may accelerate the release of peroxides. Rate of peroxide formation is not known. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.
- Incompatible materials** : Strong oxidizing agents; Acids; Perchloric acid; Reactive metals; Bases.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| Exposure Limits: | | | | |
|--------------------------------|--------------------------------------|-------------|---|------------------------------|
| <u>Chemical Name</u> | <u>ACGIH TLV</u> | | <u>OSHA PEL</u> | |
| | <u>TWA</u> | <u>STEL</u> | <u>PEL</u> | <u>STEL</u> |
| Light aromatic solvent naphtha | N/Av | N/Av | N/Av | N/Av |
| 2-Butoxy ethanol | 20 ppm | N/Av | 50 ppm (skin) | N/Av |
| 1,2,4-Trimethylbenzene | 25 ppm (trimethylbenzene isomers) | N/Av | 25 ppm (trimethylbenzene isomers) (final rule limit) | N/Av |
| 1,3,5-Trimethyl benzene | 25 ppm (trimethylbenzene isomers) | N/Av | 25 ppm (trimethylbenzene isomers) (final rule limit) | N/Av |
| Xylene (mixed isomers) | 100 ppm | 150 ppm | 100 ppm (435 mg/m ³) | N/Av |
| Cumeme | 50 ppm | N/Av | 50 ppm ; 245 mg/m ³ (Skin) | N/Av |
| oleic acid | N/Av | N/Av | N/Av | N/Av |
| Heavy aromatic solvent naphtha | N/Av | N/Av | 500 ppm (as petroleum distillates, naphtha) | N/Av |
| Trimethylbenzenes | 25 ppm | N/Av | 25 ppm (final rule limit) | N/Av |
| Ethylbenzene | 20 ppm | N/Av | 100 ppm ; 435 mg/m ³ | 125ppm; 545mg/m ³ |

Exposure controls

Ventilation and engineering measures

- : Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use non-sparking equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

SAFETY DATA SHEET

- Skin protection** : Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye / face protection** : Wear eye/face protection. Chemical splash goggles are recommended. A full face shield may also be necessary.
- Other protective equipment** : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.
- General hygiene considerations** : Avoid breathing mist or vapor. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : Amber liquid.
- Odour** : Mineral oil odour.
- Odour threshold** : N/Av
- pH** : N/Av
- Melting/Freezing point** : N/Av
- Initial boiling point and boiling range** : 113 - 116 °C / 235 - 240°F
- Flash point** : >60°C / >140°F
- Flashpoint (Method)** : Tag closed cup
- Evaporation rate (BuAe = 1)** : Slower than n-butyl acetate
- Flammability (solid, gas)** : N/Av
- Lower flammable limit (% by vol.)** : N/Av
- Upper flammable limit (% by vol.)** : N/Av
- Oxidizing properties** : None known.
- Explosive properties** : N/Av
- Vapour pressure** : N/Av
- Vapour density** : >1
- Relative density / Specific gravity** : 0.90
- Solubility in water** : Slightly soluble.
- Other solubility(ies)** : N/Av
- Partition coefficient: n-octanol/water or Coefficient of water/oil distribution** : N/Av
- Auto-ignition temperature** : N/Av
- Decomposition temperature** : N/Av
- Viscosity** : N/Av
- Volatiles (% by weight)** : 87%(approximately)
- Volatile organic Compounds (VOC's)** : N/Av
- Absolute pressure of container** : N/Av
- Flame projection length** : N/Av
- Other physical/chemical comments** : None reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

- Reactivity** : Not normally reactive.
- Chemical stability** : Stable under normal conditions.

SAFETY DATA SHEET

Possibility of hazardous reactions

: Hazardous polymerization will not occur. May be sensitive to static discharge. May form explosive peroxides during prolonged exposure to air and heat. Rate of peroxide formation is not known.

Conditions to avoid

: Keep away from flames and hot surfaces. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharge. Avoid contact with incompatible materials.

Incompatible materials

: Strong oxidizing agents; Acids; Perchloric acid; Reactive metals; Bases.

Hazardous decomposition products

: None reported by the manufacturer. Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption

: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: Toxic if inhaled. Inhalation may cause respiratory irritation and central nervous system depression. Symptoms include: Upper respiratory irritation, coughing, sneezing, staggering gait, giddiness, drowsiness, slurred speech, nausea, and possible nervous system depression.

Sign and symptoms ingestion

: Harmful if swallowed. Ingestion may cause symptoms similar to inhalation. Symptoms may include severe abdominal pain, nausea and vomiting. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing.

Sign and symptoms skin

: Toxic in contact with skin. May be absorbed through the skin, producing symptoms similar to ingestion or inhalation. Causes skin irritation. Symptoms include: Dryness, itching, cracking, burning, redness and swelling.

Sign and symptoms eyes

: Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects

: Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights. Chronic overexposure to 2-butoxyethanol may cause liver, kidney and blood damage. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Mutagenicity

: Not expected to be mutagenic in humans.

Carcinogenicity

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification Carcinogenicity- Category 2 Suspected of causing cancer.

Contains Cumene. Cumene is classified as possibly carcinogenic by IARC (Group 2B).
Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3).

Reproductive effects & Teratogenicity

SAFETY DATA SHEET

- : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification Reproductive Toxicity - Category 2 Suspected of damaging the unborn child. Developmental

Contains Xylene (mixed isomers) Xylene may cause fetotoxic effects (e.g. reduced fetal weight, delayed ossification, behavioral effects) at doses which are not maternally toxic, based on animal data.

Sensitization to material

- : Not expected to be a skin sensitizer.
Not expected to be a respiratory sensitizer.

Specific target organ effects

- : Eyes, skin, respiratory system, digestive system, central nervous system, blood system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification

Specific target organ toxicity - single exposure Category 3 May cause drowsiness and dizziness. May cause respiratory irritation.

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Medical conditions aggravated by overexposure

- : Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

- : None reported by the manufacturer.

Toxicological data

- : The calculated ATE values for this mixture are:
ATE oral = 1041.6mg/kg
ATE dermal =545.7mg/kg
ATE inhalation (vapours) =3.7mg/L/4H

See below for individual ingredient acute toxicity data.

| <u>Chemical name</u> | <u>LC₅₀(4hr)</u> | <u>LD₅₀</u> | |
|--------------------------------|--|------------------------|--|
| | <u>inh, rat</u> | <u>(Oral, rat)</u> | <u>(Rabbit, dermal)</u> |
| Light aromatic solvent naphtha | >17.7mg/L/4H (vapour) | 8400 mg/kg | >3160 mg/kg |
| 2-Butoxy ethanol | 450 ppm (2.175 mg/L) | 530 mg/kg | 400 - 500 mg/kg |
| 1,2,4-Trimethylbenzene | 18 mg/L | 5000 mg/kg | > 3160 mg/kg |
| 1,3,5-Trimethyl benzene | 24 mg/L | 23 000 mg/kg | >3160mg/kg |
| Xylene (mixed isomers) | 6350 ppm (27.6 mg/L) (vapours) | 3253 mg/kg | 12 180 mg/kg |
| Cumeme | 8000 ppm; 39 mg/L | 2260 mg/kg | 10 627 mg/kg |
| oleic acid | N/Av | >19200 mg/kg | >3000mg/kg guinea pig |
| Heavy aromatic solvent naphtha | > 17.1 mg/L/4 hours | > 6000 mg/kg | > 3160 mg/kg |
| Trimethylbenzenes | 18 - 24mg/kg (based on similar substances) | 8970 mg/kg | >3160mg/kg (based on similar substances) |
| Ethylbenzene | 4000 ppm (17.4mg/L) (vapour) | 3500 mg/kg | 15,380 mg/kg |

Other important toxicological hazards

- : None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

- : No data is available on the product itself.

See the following tables for individual ingredient ecotoxicity data.

SAFETY DATA SHEET

Ecotoxicity data:

| <u>Ingredients</u> | CAS No | Toxicity to Fish | | |
|--------------------------------|------------|---|--|----------|
| | | LC50 / 96h | NOEC / 21 day | M Factor |
| Light aromatic solvent naphtha | 64742-95-6 | 9.22 mg/L (Rainbow trout) | N/Av | None. |
| 2-Butoxy ethanol | 111-76-2 | 1490 mg/L (Lepomis marcrhius) | >100mg/L (Zebra fish) | none |
| 1,2,4-Trimethylbenzene | 95-63-6 | 7.19 - 8.28 mg/L (Fathead minnow) | N/Av | None. |
| 1,3,5-Trimethyl benzene | 108-67-8 | 12.52 mg/L (Goldfish) | N/Av | None. |
| Xylene (mixed isomers) | 1330-20-7 | 8.2 mg/L (Rainbow trout) | N/Av | None. |
| Cumeme | 98-82-8 | 4.5mg/L (Rainbow trout) | 0.38mg/L QSAR | None. |
| oleic acid | 112-80-1 | 205 mg/L (Fathead minnow) | N/Av | None. |
| Heavy aromatic solvent naphtha | 64742-94-5 | 3.6 mg/L (Rainbow trout) | N/Av | none |
| Trimethylbenzenes | 25551-13-7 | 7.72mg/L (Fathead minnow) (Read-across) | N/Av | None. |
| Ethylbenzene | 100-41-4 | 4.2 mg/L (Rainbow trout) | 1.13mg/L(30 day) QSAR (no species given) | none |

| <u>Ingredients</u> | CAS No | Toxicity to Daphnia | | |
|--------------------------------|------------|--|-------------------------|----------|
| | | EC50 / 48h | NOEC / 21 day | M Factor |
| Light aromatic solvent naphtha | 64742-95-6 | 6.16 mg/L (Daphnia magna) | N/Av | None. |
| 2-Butoxy ethanol | 111-76-2 | 835mg/L (Daphnia magna) | 100mg/L (Daphnia magna) | none |
| 1,2,4-Trimethylbenzene | 95-63-6 | 6.14 mg/L (Daphnia magna) | N/Av | None. |
| 1,3,5-Trimethyl benzene | 108-67-8 | 6 mg/L (Daphnia magna) | 0.4mg/L | None. |
| Xylene (mixed isomers) | 1330-20-7 | 3.2 - 9.56 mg/L (Daphnia magna) | N/Av | None. |
| Cumeme | 98-82-8 | 2.14 mg/L (Daphnia magna) | 0.35mg/L | None. |
| oleic acid | 112-80-1 | N/Av | N/Av | None. |
| Heavy aromatic solvent naphtha | 64742-94-5 | 1.1 mg/L (Water flea) | N/Av | none |
| Trimethylbenzenes | 25551-13-7 | 2.7mg/L Daphnia magna (Water flea) (Read-across) | 0.4mg/L (Read-across) | None. |
| Ethylbenzene | 100-41-4 | 1.81 mg/L/ (Water flea) | N/Av | none |

SAFETY DATA SHEET

| Ingredients | CAS No | Toxicity to Algae | | |
|--------------------------------|------------|---|-------------------------------------|----------|
| | | EC50 / 96h or 72h | NOEC / 96h or 72h | M Factor |
| Light aromatic solvent naphtha | 64742-95-6 | N/Av | N/Av | N/Av |
| 2-Butoxy ethanol | 111-76-2 | 911mg/L/72hr | 286mg/L/72hr | none |
| 1,2,4-Trimethylbenzene | 95-63-6 | N/Av | N/Av | None. |
| 1,3,5-Trimethyl benzene | 108-67-8 | 3.191mg/L QSAR | N/Av | None. |
| Xylene (mixed isomers) | 1330-20-7 | 3.2 - 4.9 mg/L/72hr (Green algae) | N/Av | None. |
| Cumeme | 98-82-8 | 1.29mg/L/72hr (Green algae) | 0.73mg/L | None. |
| oleic acid | 112-80-1 | N/Av | N/Av | None. |
| Heavy aromatic solvent naphtha | 64742-94-5 | 7.2 mg/L/72 hours (Green algae) | 0.22 mg/L/72 hours (Green algae) | none |
| Trimethylbenzenes | 25551-13-7 | 5.7mg/L/72hr (Green algae) (Read-across) | 0.38mg/L/72hr (Read-across) | None. |
| Ethylbenzene | 100-41-4 | 3.6 mg/L/96 hours (Selanastrum capricornatum) | 3.4mg/L | none |

Persistence and degradability

- : No data is available on the product itself.
The following ingredients are considered to be readily biodegradable: 2-butoxyethanol.

Bioaccumulation potential

- : No data is available on the product itself.

See the following data for ingredient information.

| Components | Partition coefficient n-octanol/ater (log Kow) | Bioconcentration factor (BCF) |
|--|--|-------------------------------|
| Light aromatic solvent naphtha (CAS 64742-95-6) | 2.1 - 6(calculated) | 10 - 2500(calculated) |
| 2-Butoxy ethanol (CAS 111-76-2) | 0.81 at 25 °C | 0.97 |
| 1,2,4-Trimethylbenzene (CAS 95-63-6) | 3.78 | 31 - 275 |
| 1,3,5-Trimethyl benzene (CAS 108-67-8) | 3.6 - 3.93 | 23 - 328 |
| Xylene (mixed isomers) (CAS 1330-20-7) | 3.12 - 3.2 | 0.6 - 15 |
| Cumeme (CAS 98-82-8) | 3.55 at 23 °C | 224 |
| oleic acid (CAS 112-80-1) | 7.64 | 10(calculated) |
| Heavy aromatic solvent naphtha (CAS 64742-94-5) | >3 - < 6.5 | No information available. |
| Trimethylbenzenes (CAS 25551-13-7) | 3.63 | 42 - 328 |
| Ethylbenzene (CAS 100-41-4) | 3.15 | 1.1 - 1.5 |

Mobility in soil : No data is available on the product itself.

Other Adverse Environmental effects

- : The ecological characteristics of this product have not been fully investigated.
Contains material that may be harmful in the environment. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

SECTION 13. DISPOSAL CONSIDERATIONS**Handling for Disposal**

- : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

SAFETY DATA SHEET

- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

| Regulatory Information | UN Number | UN proper shipping name | Transport hazard class(es) | Packing Group | Label |
|---|---|---|----------------------------|---------------|---|
| 49CFR/DOT | NA1993 | Combustible liquid, n.o.s. (Aromatic naphtha; Trimethylbenzene) | Combustible. | III |  |
| 49CFR/DOT Additional information | Not regulated for road or rail shipment if packaged in non-bulk containers (450 Litres or less each). The 'label' appearing here is the placard to be used for bulk shipments. This product meets the criteria for an environmentally hazardous material according to the IMDG Code. | | | | |
| TDG | None. | Not regulated. | not regulated | none |  |
| TDG Additional information | This product meets the criteria for an environmentally hazardous material according to the IMDG Code. | | | | |

- Special precautions for user** : Keep away from heat, sparks and open flame. - No smoking.
- Environmental hazards** : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.
- Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**
: Not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

| <u>Ingredients</u> | CAS # | TSCA Inventory | CERCLA Reportable Quantity(RQ) (40 CFR 117.302): | SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355: | SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical | |
|--------------------------------|------------|----------------|--|--|---|--------------------------|
| | | | | | Toxic Chemical | de minimus Concentration |
| Light aromatic solvent naphtha | 64742-95-6 | Yes | N/Ap | N/Ap | No | N/Ap |
| 2-Butoxy ethanol | 111-76-2 | Yes | N/Ap | N/Av | No | N/Ap |
| 1,2,4-Trimethylbenzene | 95-63-6 | Yes | N/Ap | N/Ap | Yes | 1% |
| 1,3,5-Trimethyl benzene | 108-67-8 | Yes | N/Ap | N/Av | No | N/Ap |
| Xylene (mixed isomers) | 1330-20-7 | Yes | 100 lb/ 45.4 kg | None. | Yes | 1% |
| Cumeme | 98-82-8 | Yes | 5000 lb/ 2270 kg | N/Ap | Yes | 1% |
| oleic acid | 112-80-1 | Yes | N/Ap | N/Av | No | N/Ap |
| Heavy aromatic solvent naphtha | 64742-94-5 | Yes | N/Ap | N/Av | No | N/Ap |
| Trimethylbenzenes | 25551-13-7 | Yes | N/Ap | N/Ap | No | N/Ap |
| Ethylbenzene | 100-41-4 | Yes | 1000 lb/ 454 kg | N/Ap | Yes | 0.1% |

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SAFETY DATA SHEET**US State Right to Know Laws:**

The following chemicals are specifically listed by individual States:

| <u>Ingredients</u> | CAS # | California Proposition 65 | | State "Right to Know" Lists | | | | | |
|--------------------------------|------------|---------------------------|------------------|-----------------------------|-----|-----|-----|-----|-----|
| | | Listed | Type of Toxicity | CA | MA | MN | NJ | PA | RI |
| Light aromatic solvent naphtha | 64742-95-6 | No | Not listed | No | No | No | No | No | No |
| 2-Butoxy ethanol | 111-76-2 | No | Not listed | Yes | Yes | Yes | Yes | Yes | Yes |
| 1,2,4-Trimethylbenzene | 95-63-6 | No | Not listed | No | Yes | Yes | Yes | Yes | No |
| 1,3,5-Trimethyl benzene | 108-67-8 | No | Not listed | Yes | Yes | No | No | No | No |
| Xylene (mixed isomers) | 1330-20-7 | No | Not listed | Yes | Yes | Yes | Yes | Yes | Yes |
| Cumeme | 98-82-8 | Yes | Carcinogen | Yes | Yes | Yes | Yes | Yes | Yes |
| oleic acid | 112-80-1 | No | Not listed | No | No | No | No | Yes | No |
| Heavy aromatic solvent naphtha | 64742-94-5 | No | Not listed | No | No | No | No | No | No |
| Trimethylbenzenes | 25551-13-7 | No | Not listed | Yes | Yes | Yes | Yes | Yes | No |
| Ethylbenzene | 100-41-4 | Yes | Carcinogen: | Yes | Yes | Yes | Yes | Yes | Yes |

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

SAFETY DATA SHEET

| Ingredients | CAS # | European EINECS | Australia AICS | Philippines PICCS | Japan ENCS | Korea KECI/KECL | China IECSC | NewZealand IOC |
|--------------------------------|------------|-----------------|----------------|-------------------|------------------|-----------------|-------------|--|
| Light aromatic solvent naphtha | 64742-95-6 | 265-199-0 | Present | Present | (9)-1698 | KE-31662 | Present | May be used as a single component chemical under an appropriate group standard |
| 2-Butoxy ethanol | 111-76-2 | 203-905-0 | Present | Present | (7)-97; (2)-407 | KE-04134 | Present | HSR001154 |
| 1,2,4-Trimethylbenzene | 95-63-6 | 202-436-9 | Present | Present | (3)-7; (3)-3427 | KE-34410 | Present | HSR001382 |
| 1,3,5-Trimethyl benzene | 108-67-8 | 203-604-4 | Present | Present | (3)-7; (3)-3427 | KE-34411 | Present | HSR001229 |
| Xylene (mixed isomers) | 1330-20-7 | 215-535-7 | Present | Present | (3)-60; (3)-3 | KE-35427 | Present | HSR000983 |
| Cumeme | 98-82-8 | 202-704-5 | Present | Present | (3)-32; (3)-22 | KE-23957 | Present | HSR001184 |
| oleic acid | 112-80-1 | 204-007-1 | Present | Present | (2)-975; (2)-609 | KE-26450 | Present | HSR003153 |
| Heavy aromatic solvent naphtha | 64742-94-5 | 265-198-5 | Present | Present | (3)-7 | KE-31656 | Present | May be used as a single component chemical under an appropriate group standard |
| Trimethylbenzenes | 25551-13-7 | 247-099-9 | Present | Present | (3)-7; (3)-3427 | KE-34408 | Present | May be used as a single component chemical under an appropriate group standard |
| Ethylbenzene | 100-41-4 | 202-849-4 | Present | Present | (3)-60; (3)-28 | KE-13532 | Present | HSR001151 |

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
 ATE: Acute Toxicity Estimate
 AICS: Australian Inventory of Chemical Substances
 CA: California
 CAS: Chemical Abstract Services
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
 CFR: Code of Federal Regulations
 CNS: Central Nervous System
 CSA: Canadian Standards Association
 DOT: Department of Transportation
 EC50: Effective Concentration 50%.
 EINECS: European Inventory of Existing Commercial chemical Substances
 ENCS: Existing and New Chemical Substances
 EPA: Environmental Protection Agency
 HMIS: Hazardous Materials Identification System
 HSDB: Hazardous Substances Data Bank
 IARC: International Agency for Research on Cancer
 Inh: Inhalation
 IMDG: International Maritime Dangerous Goods
 KECI: Korean Existing Chemicals Inventory
 KECL: Korean Existing Chemicals List
 LC: Lethal Concentration
 LD: Lethal Dose
 MA: Massachusetts
 MN: Minnesota
 MSHA: Mine Safety and Health Administration
 N/Ap: Not Applicable
 N/Av: Not Available
 NFPA: National Fire Protection Association

SAFETY DATA SHEET

NIOSH: National Institute of Occupational Safety and Health
 NOEC: No observable effect concentration
 NTP: National Toxicology Program
 NJ: New Jersey
 NOEC: No observable effect concentration
 OECD: Organisation for Economic Co-operation and Development
 OSHA: Occupational Safety and Health Administration
 PA: Pennsylvania
 PEL: Permissible exposure limit
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 RCRA: Resource Conservation and Recovery Act
 RI: Rhode Island
 RTECS: Registry of Toxic Effects of Chemical Substances
 SARA: Superfund Amendments and Reauthorization Act
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 TPQ: Threshold Planning Quantity
 TSCA: Toxic Substance Control Act
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Identification System

References : Canadian Centre for Occupational Health and Safety (CCOHS), CCIInfoWeb databases, 2015 (CHEMINFO, HSDB and RTECS).
 OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015
 European Chemicals Agency, Classification Legislation, 2015
 Material Safety Data Sheet from manufacturer
 Information taken from reference works and the literature.

Preparation Date (mm/dd/yyyy) : 05/31/2015

Other special considerations for handling : Provide adequate information, instruction and training for operators.

| | |
|---|--|
| <p>Prepared for: FPPF Chemical Company, Inc. 117 West Tupper Street Buffalo, NY, USA 14201 Telephone: 1-800-735-3773 Please direct all enquiries to FPPF Chemical Company</p> | |
| <p>Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p> |  |

DISCLAIMER

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from FPPF Chemical Company, Inc and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and FPPF Chemical Company, Inc.

END OF DOCUMENT