



Technol® STR-2+®

Fuel Oil Conditioner

Material Safety Data Sheet II

Section 5. Physical Characteristics.

ODOR : Camphor.
 MATERIAL IS : Liquid.
 FLASH POINT : 126F Closed Cup.
 APPEARANCE : Blue-Green.
 BOILING POINT : < 340F.
 VAPOR DENSITY : >1.
 VOLATILES BY VOLUME : (@20°C): Nil.
 SPECIFIC GRAVITY @25°C (77F): 0.91.

pH : N/A.
 LBS PER GALLON : 7.60.
 SOLUBILITY IN WATER: Negligible.
 VAPOR PRESSURE (mm Hg@20°C): <5.
 EVAPORATION RATE:
 (Butyl Acetate=1): <1.

Section 6. Reactivity Data.

STABILITY : Product is stable.
 INCOMPATIBILITY : Strong oxidizing agents.
 CONDITIONS TO AVOID : Extreme heat and fire.
 HAZARDOUS POLYMERIZATION : Will not occur.
 HAZARDOUS DECOMPOSITION : Like all organic compounds and mixtures, extreme heat will generate Carbon Monoxide, Carbon Dioxide and water.

Section 7. First Aid Measures.

INHALATION : Remove to fresh air - get medical attention.
 EYE CONTACT : Rinse in cool, flowing water for 15 minutes; get medical attention.
 SKIN CONTACT : Wash with soap and water get medical attention if skin irritation persists.
 INGESTION : Get medical attention immediately. **DO NOT INDUCE VOMITING;** Give Artificial Respiration if breathing stops.

Section 8. Environmental Concerns.

DEGRADABILITY/AQUATIC TOXICITY : Not Known.
 RCRA STATUS OF UNUSED MATERIAL : Dispose in permitted hazardous waste site.
 EPA HAZARDOUS SUBSTANCE: Yes - Reportable Quantity = 100 lbs. for Ignitable substance.
 WASTE DISPOSAL METHODS: Incinerate as a waste oil at a registered site; disposer must comply with Federal, State and Local disposal or discharge statutes.

Section 9. References.

GENERAL: Merck Index, Tenth Edition; Supplied Material Safety Data.
 PERMISSIBLE CONCENTRATION REFERENCES: ACGIH, NIOSH, OSHA; See *Registry of Toxic Effects of Chemical Substances* for specific test results and the latest regulatory standards.



Technol Fuel Conditioners, Inc.

REV 906

Tel: 800 645-4033

www.technol.com

Fax: 732 542-0109